
## A portable and stationary mounted unit all in one







#### Easy to Use Detergent System - Improved cleaning performance:

The SC UNO 4M PS range include the **FoamSprayer** technology, which allows a simple and efficient application of detergent. The detergent foam is easily sprayed on the dirty items and will stick to the dirt while dissolving it. Use of the FoamSprayer saves time and detergent while being externely easy and efficient.





### A true "two-in-one" machine

The Nilfisk SC UNO 4M PS is both a stationary and a portable unit. A simple and intuitive to use, cost effective fixed installation on the wall or as a portable model, carried from site to site to different working place. Delivered with all accessories for immediate use.

Designed for medium cleaning tasks the SC UNO 4M PS serie is a reliable choice for light agriculture, building and construction and automotive areas, etc. The key objective is to deliver one unique versatile machine for professionals with different demands as to cleaning environment.

#### Portable or Stationary Design

SC UNO 4M PS models can be easily carried from site to site with the robust, steel transport handle. The steel transport handle protects the plastic cabinet parts from damage.

SC UNO 4M PS models can also be placed in a fixed installation against a wall thanks to the designed installation plate. The model is then placed out of the way, permanently ready for use and not taking up any valuable floor space.

Thanks to the flexible design, it can quickly be removed from the wall fixation and again be used as a portable unit and moved to a different site if the user has several applications.

#### The SC UNO 4M PS is equipped with:

- Powered by 1450 rpm high efficiency motor (50 Hz)
- Brass pump head
- 3 ceramic coated pistons
- Pressure activated unloader system
- Enclosed oil system
- Robust, steel transport handle

The unit can operate both in vertical and in horizontal position.

#### **Extra Selling points**


- Light weight
- Robust steel handle for easy transport



The **FoamSprayer** technology allows a simple and efficient application of detergent.







Pump oil tank with oil level sight and fill/empty function

# Innovative range offering reduced running costs, greater cleaning efficiency and easier overall handling

- Brass pump head
- Pressure activated unloader system
- Easy connection of Gun, FoamSprayer and FlexoPower Plus lance
- •Oil plug, and extra oil canister for wall mount
- Optimal maintenance with easy service functions
- •External oil level sight
- Ergo couplings
- FoamSprayer



#### **TECHNICAL SPECIFICATIONS**

Description	SC UNO 4M-140/620 PS	SC UNO 4M-160/720 PS
Item no.	107340500	107340501
Pump pressure (bar/MPa)	140/14	160/16
Cleaning impact (kg/force)	2.7	3.4
Water flow Qmax/Qiec (I/h)	620/560	720/660
Max. inlet temperature (°C)	60	60
Pump (RPM)	1450	1450
Dimensions L x W x H (mm)	480x240x340	480x240x340
Weight (kg)	34	34
Power consumption (kW)	2.9	3.5
Voltage/phase/frequency/current (V/~/Hz/A)	230/1/50/12.5	400/3/50/6.5
El cable (m)	5	5
Suction height dry / wet (m)	0.5 / 1	0.5 / 1
Nozzle size	.0340	.0400
Features:		
Pistons / number of pistons	Ceramic coated / 3	Ceramic coated / 3
Automatic start/stop	•	•
FoamSprayer attachment	•	•
Detergent tank, liter	1	1
Standard equipment:		
HP hose (DN6 10 m)	301002275	301002275
Ergo 2000 incl. swivel	106403122	106403122
Ergo coupling	101119496	101119496
Water inlet coupling, Gardena	32541	32541
FlexoPower Plus lance	106402282	106402282
Tornado Plus nozzle	101119735	101119738



Kornmarksvej 1 · DK-2605 Brøndby · Denmark Tel.: +45 43 23 81 00 · Fax: +45 43 43 77 00 mail.com@nilfisk.com www.nilfisk.com



