

The fastest way to collect trims in 1,1 kW and 150 liters container

Model R 155 is equipped with a 1,1 kW threephase motor and a 150 liters container. It mounts a nylon filter, however specific filters for dust extraction are available. The threephase suction unit is placed under the container, the liner is spread out and completely open and all product vacuumed in is neatly compacted on the bottom, optimizing the container capacity.

- Small
- No maintenance needed
- Silent
- Easy and quick disposal of waste material
- High capacity
- Quick visual level control: plexiglass port-hole in the lid
- Specific liner filter for fine dust available
- Stainless steel version

Industrial vacuum for the collection of plastic, paper or textile trims. Its suction power, its features and its size make it the right vacuum to operate in packaging areas.



Picture shown may not represent model quoted

• Standard equipment

• Standard equipment

Model	R155 V 2ID50	R155 V	R155 X
Ref. no.	4031600024	4031600027	4031600035

PRODUCT FEATURES

Filter bag	•	•	•
Stainless steel filter chamber			•
Switch motor protector	•	•	•
Earth connection			
5 pin plug			
Conductive wheels			
Clapet valve			
Inspection window	•	•	•
Silencer			
N°2 inlets	•		



The fastest way to collect trims in 1,1 kW and 150 liters container

Model	R155 X 2ID50	R155 X ID70
Ref. no.	4031600037	4031600038

PRODUCT FEATURES

Filter bag	•	•
Stainless steel filter chamber	•	•
Switch motor protector	•	•
Earth connection		
5 pin plug		
Conductive wheels		
Clapet valve		
Inspection window	•	•
Silencer		
N°2 inlets		

Technical specifications	R155 V 2ID50	R155 V	R155 X
Voltage (V)	400	400	400
Frequency (Hz)	50	50	50
Ip protection class	55	55	55
Insulation class	F	F	F
Rated power (W)	1100	1100	1100
Airflow without hose (l/sec)	55	55	55
Vacuum max (kPa)	21	21	21
Sound pressure level at 1.5 m (dB(A) ISO 3744)	72	72	72
Container capacity (l)	150	150	150
Main filter type	NYLON MOD. R560	NYLON MOD. R560	NYLON MOD. R560
Main filter area (cm²)	14.350	14.350	14.350
Inlet (mm)	50	50	50
Length x width x height (cm)	65 x 65 x 125	65 x 65 x 125	65 x 65 x 125
Weight (kg)	61	61	61









Technical specifications	R155 X 2ID50	R155 X ID70
Voltage (V)	400	400
Frequency (Hz)	50	50
Ip protection class	55	55
Insulation class	F	F
Rated power (W)	1100	1100
Airflow without hose (l/sec)	55	55
Vacuum max (kPa)	21	21










The fastest way to collect trims in 1,1 kW and 150 liters container

Technical specifications	R155 X 2ID50	R155 X ID70
Sound pressure level at 1.5 m (dB(A) ISO 3744)	72	72
Container capacity (l)	150	150
Main filter type	NYLON MOD. R560	NYLON MOD. R560
Main filter area (cm ²)	14.350	14.350
Inlet (mm)	50	50
Length x width x height (cm)	65 x 65 x 125	65 x 65 x 125
Weight (kg)	61	61





● Standard equipment, ○ Supplementary accessories, □ Mountable equipment

Accessories	Ref. no.	Min. required	R155 V 2ID50	R155 V	R155 X
Hose Vacuum Cleaner					
	50MM ANTI STATIC CUFF	Z7 20325	0	○	○
	ANT.POL BLACK HOSE D50 MT3+SLEEVES	Z7 22369	0	○	○
	ANT.POL BLACK HOSE D50 MT5+SLEEVES	Z7 22372	0	○	○
	ANT.POL BLACK HOSE D50 MT15+SLEEVES	4072200478	0	○	○
	FLEX CONDUCTIVE HOSE D50 MT3+ SLEEVES	Z7 22375	0	○	○
	FLEX CONDUCTIVE HOSE D50 MT5+ SLEEVES	Z7 22377	0	○	○
	FLEX CONDUCTIVE HOSE D50 MT15+ SLEEVES	4072200481	0	○	○
	FLOWING PTFE SLEEVE D50	Z7 20326	0	○	○

The fastest way to collect trims in 1,1 kW and 150 liters container











Accessories	Ref. no.	Min. required	R155 V 2ID50	R155 V	R155 X
 HANK CONDUCTIVE FLEX HOSE D50 MT.30	4072400234	0	○	○	○
 POL HOSE D50 MT5+SLEEVES	Z7 22366	0	○	○	○
 POL HOSE D50 MT15+SLEEVES	4072200475	0	○	○	○
 SLEEVE D50 PVC	Z7 23023	0	○	○	○
 SLEEVE D50 RUBBER	Z7 20002	0	○	○	○
 SLEEVE D50ANTISTAT.RUBBER COMPONENT ATEX	40000219	0	○	○	○
 TUBE D50 POLYURETHAN MT3+SLEEV	Z7 22298	0	○	○	○

● Standard equipment, ○ Supplementary accessories, □ Mountable equipment

Accessories	Ref. no.	Min. required	R155 X 2ID50	R155 X ID70
Hose Vacuum Cleaner				
 50MM ANTI STATIC CUFF	Z7 20325	0	○	○
 ANT.POL BLACK HOSE D50 MT3+SLEEVES	Z7 22369	0	○	○
 ANT.POL BLACK HOSE D50 MT5+SLEEVES	Z7 22372	0	○	○
 ANT.POL BLACK HOSE D50 MT15+SLEEVES	4072200478	0	○	○



The fastest way to collect trims in 1,1 kW and 150 liters container

Accessories	Ref. no.	Min. required	R155 X 2ID50	R155 X ID70
 FLEX CONDUCTIVE HOSE D50 MT3+ SLEEVES	Z7 22375	0	○	○
 FLEX CONDUCTIVE HOSE D50 MT5+ SLEEVES	Z7 22377	0	○	○
 FLEX CONDUCTIVE HOSE D50 MT15+ SLEEVES	4072200481	0	○	○
 FLOWING PTFE SLEEVE D50	Z7 20326	0	○	○
 HANK CONDUCTIVE FLEX HOSE D50 MT.30	4072400234	0	○	○
 POL HOSE D50 MT5+SLEEVES	Z7 22366	0	○	○
 POL HOSE D50 MT15+SLEEVES	4072200475	0	○	○
 SLEEVE D50 PVC	Z7 23023	0	○	○
 SLEEVE D50 RUBBER	Z7 20002	0	○	○
 SLEEVE D50ANTISTAT.RUBBER COMPONENT ATEX	40000219	0	○	○
 TUBE D50 POLYURETHAN MT3+SLEEV	Z7 22298	0	○	○